



## Treating Water Mold in a Baquacil<sup>®</sup> or Baquacil<sup>®</sup> CDX<sup>®</sup> Pool

### POOL SHOULD BE CONVERTED TO THE BAQUACIL<sup>®</sup> CDX<sup>®</sup> SYSTEM

1. **MOST IMPORTANT MANDATORY STEP TO PERFORM:** Chemically clean the filter with **BAQUACIL<sup>®</sup> UNIVERSAL FILTER CLEANER** per label directions or change the sand and make sure filter is operating correctly. Filter should build backpressure when it is operating correctly over time (check and monitor the pressure gauge on the filter). For this treatment to work effectively, do not move to the next step before performing step 1.
- 2(a). **IF POOL BOTTOM IS VISIBLE:** Add **BAQUACIL<sup>®</sup> FLOCCULANT** as a filter aid to the skimmer per label directions while pump is running (follow **FILTER AID** instructions on the label).
- 2(b). **IF POOL BOTTOM IS NOT VISIBLE:** Broadcast **BAQUACIL<sup>®</sup> FLOCCULANT** per label directions (follow **POOL FLOCCULANT** instructions on the label). Allow the floc to settle with the pump off for 24-48 hours and then vacuum the settled debris to waste.
3. Add **BAQUACIL<sup>®</sup> LINE CLEAN** at the rate of 2 lbs. per 10,000 gallons to the skimmer(s) with the pump running. Filter continuously for 24-48 hours. Then move to the next step.
4. Test and adjust the **BAQUACIL<sup>®</sup> SWIMMING POOL SANITIZER AND ALGISTAT** level to 50 ppm and add the start-up dosages of **BAQUACIL<sup>®</sup> OXIDIZER** (1 gallon/10,000 gallons) and **BAQUACIL<sup>®</sup> CDX<sup>®</sup>** (1 pint/10,000 gallons) per label directions.
5. Continuously filter until pool is clear and check to make sure filter backpressure increases over time. If not, check the filter components and media to make sure they are in correct working condition. Backwash or clean the filter as necessary per filter manufacturer's instructions.
6. To prevent the mold from re-occurring, clean inside the skimmer(s), pump baskets, under the ladder steps, behind the light fixture (if equipped), and any other hidden areas.
7. If pool still has water mold, repeat steps above or see your Authorized Dealer for advice on how to proceed.
8. Follow the **BAQUACIL<sup>®</sup> CDX<sup>®</sup>** weekly maintenance system.